

PHOENIX TITAN 24 LOW SPEED SPECIFICATIONS

MOTOR:

- Kawasaki FD541V 17 hp Air Cooled V-Twin
- UL Approved
- Operating Noise Level 84 db
- Oil Filter
- Muffler Including Spark Arrester
- 12V Battery Start
- Full Warning System Includes Lights and Low Oil Pressure/Auto Shut Off Engine Switch

GEARING:

- Belt Drive
- Dual V Belts
- 1250 rpm Pad Speed

ADJUSTABLE PAD PRESSURE BY WAY OF TRANSFERRABLE WEIGHT:

- 25# to 55#

MACHINE MAIN FRAME

- 7 Gauge Steel
- Surface Finish Powder Coat
- Built in Spray Pump
- Center Feed Spray
- Gallon Spray Bottle Holder

UPPER HANDLE:

- Adjustable
- Built in Hour Meter
- Kill Switch

24" PAD HOLDER:

- Foam Insert
- Large Mouth Center Lock (Quick Release)

MISCELLANEOUS:

- Weight 250#
- Height 41"
- Length 56"

OPTIONS:

- Emission monitor which will first warn by way of light and horn, then shutdown when emissions exceed a specified point.
- Automatic Spray Device
- Automatic Pad Change Reminder